

SmartScan 50

Smartlite

SmartScan 25

4-wire, 2-part ultrasonic continuous level measurement of liquids, open channel flow and solids.

SmartScan™ non-contact ultrasonic continuous level measurement of liquids, solids and open channel flow, sets new in reliability, repeatability, and accuracy under extremely harsh conditions. Drawing on Patented technology, SmartScan™ supports a full range of process monitoring and storage level measurement applications. The SmartScan™ family of products includes SmartLite™, SmartScan™ 50 and SmartScan™25 covering a full application range of the target industries: water, wastewater, petrochemical, chemical, food and beverage. The SmartScan™ Family is approved for installation in Hazardous areas (Ex) and supports the Modbus RTU communication protocol.

The Smart family Offers

- RS-495 or RS-232 and 4-20mA communication
- Installation in hazardous areas (Ex)
- Easy Installation and Handling
- Graphic LCD with 6 digits and multiple indications
- The control unit can be located up to 200m away from the sensor

SmartLite™

- Our entry level cost effective product
- Designed for liquid applications
- Excellent chemical resistance (FVDF or Polypropylene are available)
- 2 SPDT Relays
- Modbus (read only)

SmartScan™ 50

- Designed for challenging harsh environment:
 - Overcomes vapors, agitators and light foam
 - High temperature range (-40°C to 90°C, -40°F to +194°F)
 - Pressure up to 5 Bar
 - Approved for installation in hazardous areas (Ex)
- Perfect for waste water applications and Open Channel Flow measurements
- Measuring range up to 12m /39.4 ft
- May be applied in liquid, solid and open channel flow applications
- Modbus RTU
- Five independent SPDT relays
- Embedded firmware for advanced calculations of volume and flow totalization
- Rapid response with high accuracy

SmartScan™ 25

- Extended range applications - up to 40 meters /131 ft
- Best fit high process tanks, large storage vessels, for dust free Solids
- Modbus (read only)
- Five independent SPDT relays
- Embedded firmware for advanced calculations of volume and flow totalization



Applications

Water & Waste water
Chemical processes
Petrochemicals
Food & Beverage industries



Data Sheet

Model		SmartScan50™	SmartLite™	SmartSean25™
Type		Ultrasonic 4-wire	Ultrasonic 4-wire	Ultrasonic 4-wire
Max range for liquids		12 meter/39.4ft	10 meter / 32ft	40 meter / 131ft
Max range for solids		8.5m/28ft	-	30m/98ft
Min range		0.40 meter / 1.3ft	0.60 meter/2ft	0.60 meter / 2ft
Measuring accuracy		0.2% of max range" (2.4cm max)	0.25% of max range* (2.5cm max)	0.25% of max range" (6.25 cm max)
Transmission frequency		50KHz	25KHz	25KHz
Power Supply		18-30VDC or 100-240VAC (option)	18-30VDCor 100-240VAC (option)	18-30VDC or 100-24CVAC (option)
Load		750 ohm@24VDC	750 ohm@24VDC	750 ohm@24VDC
Output signal		4-20mA	4 - 20mA	4 - 20mA
Communication		RS-232\RS-485 (optional)	RS-232\RS-485 (optional)	RS-232\RS-485 (optional)
Protocol		Modbus (optional)	Modbus (read only)(optional)	Modbus (read only) (optional)
Material	Main unit	ABS+UV	ABS+UV	ABS+UV
	Sensor	Glass filled polyester + Polypropylene or PVDF	Polypropylene or PVDF	Polypropylene or PVDF
	Acoustic window	Glass Reinforced Epoxy	ECTFE	ECTFE
Mounting thread		V'BSP or "NPT	1" and 2" BSP or NPT	1" and 2" BSP or NPT
Main Unit Operating Temperature		-40°c to +60°c (-40°F to + 140°F)	-40°c to +60°c (-40°F to + 140°F)	-40°c to +60°c (-40°F to + 140°F)
Sensor operating Temperature		-40°c to +90°c (-40°F to + 194°F)	-40°c to +80°c (-40°F to + 176°F)	-40°c to +80°c (-40°F to + 176°F)
Main unit Protection		IP 65	IP 65	IP 65
Sensor Protection		IP 67	IP 67	IP 67
Display		LCD (6 digits)	LCD (6 digits)	LCD (6 digits)
Maximum range of control unit (display) from sensor		200 meter	200 meter	200 meter
Cable connection		4 X Conduit 1/2" NPT or Gland (M20 option)	4 X Conduit 1/2" NPT or Gland (M20 option)	4 X Conduit 1/2" NPT or Gland (M20 option);
Mounting		Wall mount	Wall mount	Wall mount
Relays		5SPDT	2SPDT	5SPDT
Main unit Weight		1.1 Kg	1.1 Kg	1.1 Kg
Sensor Weight		0.5 Kg	0.4 Kg	0.4 Kg
Enclosure dimensions		Approx 28 x 20 x 9 cm3	Approx 28 x 20 x 9 cm3	Approx 28 x 20 x 9 cm3
Certifications		CE and ATEX, , NEPSI (optional)	CE and ATEX, NEPSI (optional)	CE andATEX, . NEPSI (optional)

* Tested in a controlled laboratory environment at room temperature.

По вопросам продаж и поддержки обращайтесь:
 Волгоград (844)278-03-48 Воронеж(473)204-51-73 Екатеринбург (343)384-55-89 Казань (843)206-01-48
 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Москва (495)268-04-70 Нижний Новгород (831)429-08-12
 Новосибирск (383)227-86-73 Ростов-на-Дону (863)308-18-15 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78 Уфа (347)229-48-12
 единый адрес: grg@nt-rt.ru